

Precision Frameworks

Framed Mirror Solutions

LED Mirrors



L-5014F - 23-5/8"(w) x 31-1/2" (h)*

L-5030F - 30"(w) x 42" (h)**

L-5054F - 54"(w) x 42" (h)**



L-5018V - 23-5/8"(w) x 31-1/2" (h)*

HARD-WIRED LED ILLUMINATED MIRRORS

Frameless Clear Mirror

Features	Benefit
Silicone gasket	Tight seal of gasket which protects against moisture
Powder coated metal housing	Protection against corrosion
Silicone wrapped LED lights	Protection against moisture and silicone will not discolour or haze over time
LED's are fastened to metal housing with clip strips	Other manufacturers use doubled sided tape to fasten the LED's which can lose adhesion
Slim design metal housing	Mirror profile is close to the wall
Operation life expectation of up to 50,000 hr	This is over 5 years of continuous operation, or over 11 years of 50% operation
Superior visibility	LED provides a crisp and clear white light imitating natural daylight

* can be hung horizontally or vertically **can only be hung as dimensions describe

Specifications

- LED Strip: 5050
- Lumens: 1884-4800
- Watts: 35W
- Colour Lumen Index: 70-80
- Colour Temperature: 6000K
- Rated hrs: 50,000
- 3mm/5mm clear mirror glass with polished edge
- UL/CE Certified
- Binning Colour Variance: White

office: 877.739.1169

fax: 678.392.4870

email: sales@pfwks.com

www.PrecisionFrameworks.com

rev. 4/18